

## MONITOR ST SPECIFICATIONS

<b>Audio Inputs</b>	(1) DB25 (four balanced stereo pairs); (1) balanced stereo aux on (2) XLR jacks; (1) unbalanced TS remote mic
<b>Audio Outputs</b>	(1) DB25 (four balanced stereo pairs); (1) stereo unbalanced XLR Cue; (1) mono balanced XLR Slate; (1) TRS stereo headphone
<b>Additional Ports</b>	(1) XLR talkback remote switch; (1) RJ-45 remote
<b>Nominal Operating Level</b>	+4 dBu
<b>Nominal Input Level</b>	+4 dBu or -10 dBV
<b>Dynamic Range</b>	110 dB
<b>Maximum Level</b>	+25 dBu
<b>Frequency Response</b>	1 Hz–100 kHz within 0.2 dB
<b>Interchannel Crosstalk</b>	-95 dB
<b>Lowpass Filter</b>	57 Hz, 3-pole Bessel/Chebyshev hybrid
<b>Total Harmonic Distortion + Noise</b>	0.002%
<b>Power Consumption</b>	30W
<b>Dimensions</b>	main unit: 1U $\times$ 9.5" (D); remote: 12" (W) $\times$ 1.5" (H) $\times$ 3.5" (D)
<b>Weight</b>	main unit: 9 lbs. (approx.); remote: 2.5 lbs. (approx.)