



## EDIROL R-09HR SPECIFICATIONS

Number of Tracks	2 (1 stereo track)
A/D/A Conversion	24-bit, 44.1/48 kHz
Frequency Response	20 Hz–40 kHz ( $\pm 2$ dB)
Data Formats (Recording)	
Format	MP3
Sampling Rates	44.1, 48 kHz
Bit Rates	64, 96, 128, 160, 192, 224, 320 Kbps
Format	WAV
Sampling Rates	44.1, 48, 88.2, 96 kHz
Bit Depths	16, 24 bits
Data Formats (Playback)	
Format	MP3
Sampling Rates	32, 44.1, 48 kHz
Bit Rates	32–320 Kbps or VBR (variable bit rate)
Format	WAV
Sampling Rates	32, 44.1, 48, 88.2, 96 kHz
Bit Depths	16, 24 bits

## EDIROL R-09HR SPECIFICATIONS

I/O	
Internal Microphone	stereo omnidirectional condenser
Mic Input	(1) stereo unbalanced 3.5 mm minijack for plug-in-powered condenser mics; $-33$ dBu nominal input level (variable)
Line Input	(1) stereo unbalanced 3.5 mm minijack; $+2$ dBu nominal input level (variable)
Headphone Output	(1) stereo 3.5 mm minijack
USB Interface	Mini-B type, supports USB 2.0 and 1.1
Effects	
Playback Reverb	4 types (Hall 1, Hall 2, Room, Plate)
Speed Change	50–150% of normal
Miscellaneous	
Storage	SD memory card (32 GB maximum capacity); 512 MB card included
Display	OLED, $128 \times 64$ -pixel graphic
Power Supply	AC adapter, (2) AA batteries
Dimensions	2.5" (W) $\times$ 1.06" (H) $\times$ 4.5" (D)
Weight	7 oz. (including batteries and memory card)