

LIQUID MIX SPECIFICATIONS

| | |
|------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Computer Connection | IEEE 1394 (FireWire) 400 |
| Power | supplied by 6-pin FireWire or 12V external power supply (included) |
| Platforms | Windows XP SP2; Mac OS X 10.3.9 or later |
| Computer CPU Required | 1.4 GHz Intel or 2 GHz Pentium (PC); 800 MHz G4 minimum, 1.5 GHz G4 recommended (Mac) |
| Computer Memory Required | 256 MB minimum, 512 MB recommended |
| Plug-in Formats | AU (Mac only); VST; RTAS (with included wrapper) |
| Sampling Rates | 44.1, 48, 88.2, 96, 192 kHz |
| Latency | 2,056 samples (47 ms at 44.1 kHz, 11 ms at 192 kHz) |
| Number of Instances | 32 mono or 16 stereo at 44.1 and 48 kHz; 8 mono or 4 stereo at 88.2 and 96 kHz; 2 mono or 1 stereo at 192 kHz |
| Number of EQ Models | 20 |
| Number of Compressor Models | 40 |
| Maximum Number of EQ Bands | 7 |
| Dimensions | 8.5" (W) × 1.5" (H) × 6" (D) |
| Weight | 1.75 lbs. |