



GIBSON HD.6-X PRO SPECIFICATIONS

Guitar	
Scale Length	24.75"
Headstock	peghead pitch: 17; platinum knurled tuners
Neck	hand-oiled mahogany; rounded, 1950s profile
Fingerboard	ebony; block carbon-fiber inlays; 22 frets
Body	single-cutaway, solid body; maple top, blue metallic finish; mahogany back
Controls	(2) volume; (2) tone; 3-way-toggle pickup switch
Bridge	Tune-o-matic
Pickups	(1) Gibson 498T analog humbucker (bridge position); (1) Gibson 490R analog humbucker (neck position); (1) Gibson hex681-2031 (6-way digital humbucker between bridge and bridge pickup)
Tailpiece	stop bar
Strings	hex-optimized (.011, .014, .020W, .028W, .038W, .050W)
Jack Plate I/O Connections	(1) ¼" TS output (analog humbuckers); (1) ⅛" TRS headphone output (w/continuously variable volume control); (1) RJ45 digital I/O (for Cat-5); (1) balanced ⅛" miniplug mic input with undefeatable 5V phantom power
BoB Breakout Box	
Modes	Classic (mono), 2x3 (stereo), Hex (6-channel)
Analog Outputs	(6) balanced/unbalanced ¼" TRS
Classic Mode Analog (mono) Output	(1) balanced/unbalanced ¼" TRS
Microphone Output	(1) balanced/unbalanced ¼" TRS
L/R Monitor Inputs	(2) balanced/unbalanced ¼" TRS
Digital I/O	RJ45 (for Cat-5)