

## NRV10 SPECIFICATIONS

<b>Analog Inputs</b>	(4) balanced ¼" TRS mono line; (4) ¼" TS mono line (2 stereo pairs); (5) XLR mic
<b>Analog Outputs</b>	(2) balanced ¼" TRS main; (2) balanced ¼" TRS control room; (2) balanced XLR main; (2) ¼" aux send; (1) ¼" TRS stereo headphone
<b>Inserts</b>	(4) ¼" TRS channel
<b>Digital I/O</b>	(2) FireWire 400
<b>Resolution, Sampling Rate</b>	24-bit, 96 kHz
<b>EQ</b>	3-band (80 Hz, 2.5 kHz, 12 kHz) on each channel
<b>Onboard Digital Effects</b>	16 (one at a time)
<b>Frequency Response (digital audio interface)</b>	20 Hz–60 kHz ±0.1 dB
<b>Frequency Response (analog line outputs)</b>	20 Hz–60 kHz ±0.1 dB
<b>Meters</b>	13-step stereo LED
<b>Phantom Power</b>	48V (globally switched)
<b>Power</b>	12 VDC
<b>Dimensions</b>	10.4" (W) × 4" (H) × 14.2" (D)
<b>Weight</b>	8.2 lbs.