

ONYX SATELLITE SPECIFICATIONS

| | |
|-------------------------------|---|
| Analog Inputs (base station) | (2) balanced XLR, (4) balanced ¼" TRS line, (2) unbalanced ¼" instrument, (2) ¼" TRS insert |
| Analog Inputs (pod) | (2) balanced XLR/TRS combo |
| Analog Outputs (base station) | (4) balanced ¼" TRS, (4) balanced/unbalanced ¼" aux |
| Analog Outputs (pod) | (2) balanced ¼", (2) ¼" stereo headphone |
| A/D Conversion | 24-bit; 44.1, 48, 88.2, or 96 kHz |
| Frequency Response | 20 Hz–20 kHz, ±1 dB @ 48 kHz (mic input to line output @ unity gain) |
| Distortion (THD + noise) | <0.02%, 20 Hz–20 kHz (1 kHz input @ +4 dBu, preamp at unity gain) |
| Signal-to-Noise Ratio | >103 dB (ref. +0 dBu mic input to line output @ unity gain) |
| Ports | (2) FireWire (400 Mb) |
| Dimensions (base station) | 10.8" (W) × 4.4" (H) × 7.1" (D) |
| Dimensions (pod) | 8" (W) × 2.1" (H) × 4.1" (D) |
| Weight (base station) | 6.1 lbs. |
| Weight (pod) | 1.8 lbs. |