



UNIVERSAL AUDIO DCS REMOTE PREAMP SPECIFICATIONS

Preamp Type	2-channel linkable, transimpedance mic preamp/DI
Microphone Inputs	(2) balanced XLR
Line Inputs	(2) balanced ¼" TRS (A DI, B DI); (1) balanced/unbalanced stereo ¼" TRS line (C); (1) unbalanced stereo ¼" TRS (cue)
Audio Outputs	(2) balanced ¼" TRS (preamps); (2) balanced ¼" TRS (speakers); (1) unbalanced stereo ¼" TRS line (AB stereo); (1) unbalanced stereo ¼" TRS line (cue); (1) balanced/unbalanced ¼" TRS line (talk mic)
Preamp Frequency Response	4 Hz–150 kHz +0/–3 dB
Preamp Distortion (THD + N)	0.002% @ 1 kHz, 40 dB gain, +14 dBu out
Reverb Bit Depth/Sampling Rate	20-bit, 48 kHz
Displays	(1) 3-character LED; (2) analog VU meters
Power	internal 100V, 120V, or 240V (depending on where purchased); IEC connector
Dimensions	controller 8.7" (W) × 2.65" (H) × 6.92" (D); preamp 5.74" (W) × 2.65" (H) × 5.64" (D)
Weight	controller 1.7 lbs.; preamp 4.7 lbs.